Phormium
Supporting growers since 1977

GreenTrans High Force

Crop clearance fabric

Technical data sheet

Product description

Type of product	Woven Fabric	**Application**	Indoor
Colour	White	**Polymer**	100% Polypropylene

Properties

Mechanical Properties	**Standard**	**Performance**	**Tolerance**
Tensile strength - Warp	EN ISO 10319	36 kN/m	-3,6 kN/m
Tensile strength - Weft	EN ISO 10319	13 kN/m	-1,3 kN/m
Elongation at break - Warp	EN ISO 10319	20 %	±2 %
Elongation at break - Weft	EN ISO 10319	17 %	±1,7 %
Water permeability	EN ISO 11058	20 l/m²*s	-6 l/m²*s
Shrinkage	2h at 70°C	1 %	-

Physical Properties	**Standard**	**Performance**	**Tolerance**
Weight	EN ISO 9864	140 g/m²	±14 g/m²
Length		As required	-
Width		100-110-130 cm	±2 cm

Durability	**Standard**	**Performance**	**Tolerance**
UV Stabilization	(Indoor use)	500 kLy	

19/03/2015
Version date :
2
Version n°

The information set forth in this data sheet reflects the best knowledge at the time of publication. The document is subject to change pursuant to new developments and findings. The same reservation applies to the properties of the products described. No liability is undertaken for results obtained by usage of the products and information.

Phormium NV

Weverslaan 15, 9160 Lokeren, Belgium

T: +32 (0) 9 340 98 11 / F: +32 (0) 9 348 77 02

info@phormium.com / www.phormium.com